

POWER PROTECTION AGAINST LIGHTNING KEEPS ELECTRONIC EQUIPMENT ON-LINE

An understanding of the degree to which lightning can affect microprocessor-controlled equipment is necessary when choosing among lightning protection alternatives.

TONY TAMOSAITIS, SOLA, A UNIT OF GENERAL SIGNAL, ELK GROVE VILLAGE, IL

Although most people think of lightning's potential for damage in terms of direct and catastrophic strokes, a wide variety of more subtle problems can occur as a result of indirect strokes. Lightning is capable of inducing line voltage transients — ranging from momentary spikes or faults, to longer surges or sags — in varying degrees that will affect the performance of microprocessor-controlled equipment and computers. This article examines these problems and the alternatives for protecting against them.

The phenomenon starts with a lightning arc, either cloud-to-cloud or cloud-to-earth, which generates an intense electromagnetic field. When an overhead or underground utility line intersects the field, a voltage surge is generated on the line in much the same manner that voltage is generated from the primary to the secondary windings of a transformer. The nature and severity of this transient can vary with the duration of the stroke, the magnitude of its discharge, its proximity to the line, its distance away from the equipment, and the type and size of the other equipment served by the line.

Impulses in the power-line voltage resulting from even minor lightning strokes to the utility line can exceed normal line voltage levels by 10 times or more. These high-level impulses typically cause arcing in power distribution systems. Arcing develops when positive or negative voltages and neutral (ground) elements in the power system are close enough to one another and carry sufficient potential to allow a discharge of electrical energy or sparkover from one element to another.

It has been determined that the sparkover level of most 120 to 240V

systems is approximately 6000V (Ref.: IEEE STD 587-1980). This sparkover level insures that most impulses encountered indoors are likely to have a magnitude of 6000V or less. However, voltage of this magnitude is still sufficient to damage or disrupt electronics. If they reach a computer or other sensitive piece of electronic equipment, lightning-induced transients typically create one of three possible effects. A high voltage transient can cause immediately noticeable component damage, often so high that the component cannot survive. Sharp, high-powered spikes, in other words, can destroy semiconductors and electrical devices found in sensitive electronic equipment, primarily by puncturing insulating barriers. Lesser voltage transients may not cause noticeable damage, yet they can put stress on components, causing them to degrade and then to fail a few hours, days, or weeks later. Weak transients, perhaps in the form of low energy, high frequency "noise," which are probably not capable of causing hardware damage, can be interpreted as valid digital signals and result in program errors or altered memory.

Sags — cycle-to-cycle decreases in power-line voltage — are less well known, but actually more commonly produced in electrical storms than surges or impulses. The reason is that impulse-suppression equipment used in ac distribution systems does its job by momentarily shorting the power-line (via arcing). The short circuit continues until the next zero crossing of the ac sine wave, thereby limiting the short circuit power outage duration to one-half cycle or less. While this short circuit is taking place, a portion of the downstream

power continues to move toward its load. The voltage present at the load continues to decrease until soon after the arc has extinguished. This results in a sag, or short duration brownout that is usually corrected within the next few cycles. In this fashion, lightning-induced sags can travel throughout the system, whereas impulses are attenuated quickly as they travel through the system's loads and other overvoltage protection devices.

Lightning can also create blackouts, or a total loss of power, usually by damaging power transmission equipment. These can be split-second outages — where minor damage occurs and the utility responds by switching the affected loads to other intact sources in the power ground — or they can be long-term losses, resulting from major damage such as line breaks. Momentary blackouts within a building also can occur as a result of lightning-induced surges. When, as described above, the surge initiates a short circuit at the primary distribution panel, downstream circuits throughout the building experience a brief total loss of power, rather than simply a sag in power. Even though this outage lasts no more than 1/2 cycle, a loss of this length is sufficient to disrupt some electronic equipment. Adding to the problem, the sudden return of power after the outage can appear as a secondary surge that adds another potential for damage.

CHOOSING POWER PROTECTION

Determining the best way to protect sensitive electronic equipment from lightning-induced problems will depend on the value of the function

Continued on page 342

Continued from page 106

performed by that equipment, and which kinds of power disruptions need protection. In accordance with how the two fundamental questions are answered, one of three kinds of power protection devices can be used: those that condition incoming power to eliminate the transients and noise produced by lightning; those that provide only backup emergency power in case of blackout; or, those that provide both power conditioning and backup power.

Some engineers feel that a viable alternative for maintaining clean power is to install a dedicated line (a special circuit running directly from a primary distribution transformer to the sensitive electronic load). However, dedicated lines offer only limited protection. Although they can isolate the sensitive load from noise and transients generated along other circuits in the building, they do nothing to prevent problems such as lightning-induced power effects that originate outside the building.

A variety of basic power protection devices bought in hopes of providing lightning protection for elec-




Figure 1. Ultra-Isolation Transformer.

tronics include surge suppressors, passive filters, ultra-isolation transformers, and electronic tap changers. While these simple devices do perform some selected power protection functions, their limitations must be considered.

Surge suppressors, for instance, can clip lightning-induced spikes at some absolute voltage level. However, these devices do not attenuate electromagnetic interference (EMI), making it possible for EMI to deteriorate sensitive electronic devices; nor


FIC fuseholders suppress RFI and EMI emission

(and provide blown fuse indication, too)

FIC introduces its 8500 series fuseholders which help meet today's stringent RFI/EMI emission control standards. Designed for 1/4" or 13/32" fuses, these shielded indicating and non-indicating fuseholders permit front panel mounting for easy, cost-saving accessibility.

FIC manufactures commercial and military fuseholders, fuse clips and blown fuse indicators and is a distributor of fuses, fuseholders and power line filters.

Call or write for more information.




fic
CORPORATION

12216 Parklawn Drive, Rockville, MD 20852
Toll Free: 800-638-6594
In MD: 301-881-8124 • TWX: 710-828-9809

Circle Number 234 on Inquiry Card

schiller
electronic

Superior Performers



Power Entry Modules

Schiller Series UNF

- Snap-in and screw-mount models
 - International safety marks
 - Highest-quality components
 - Compact, proven design
- 1, 2, 4 or 6 amps (leakage ≤ 4 mA)
 - 1 or 2 fuses 5x20 mm/ .25x1.25" (US)
 - Options: lighted switch, varistor, etc.
 - Voltage selector 110/120-220/240 volts pending



ITC SYSTEMS Incorporated

813 East Anapamu Street 2C
PO Box 23059 Santa Barbara, CA 93121
805/965-8900 TLX: 295 298 INTERTEL

Circle Number 229 on Inquiry Card

do they compensate for voltage sags.

Passive filters do a better job of noise reduction (although only at certain frequencies), but they are typically incapable of attenuating low frequency, high energy transients. A sufficiently forceful lightning-induced transient can blow up the device, cutting off all power to the electronic equipment. Also, these devices do nothing to counteract surges or sags.

An isolation transformer, on the other hand, can provide reasonably good common-mode surge protection and a fair amount of normal-mode surge protection, but cannot regulate voltage sags. Figure 1.

The electronic tap changer, which is based on a multi-tapped transformer combined with electronic sensing and switching, provides voltage regulation by selective switching among taps in response to input voltage. Some of these units are relatively inexpensive, although tap changer design schemes typically provide insufficient inherent noise attenuation. Consequently, noise protection devices such as surge suppressors, line filters and filter capacitors are usually provided at additional cost. These added devices still exhibit all of the limitations described earlier. Tap changers do not provide smooth, continuous adjustments of output voltage. Instead, they respond in steps typically ranging from $\pm 13\%$ to $\pm 17\%$ of nominal output voltage. Figure 2.

As lightning protection devices, none of the above four designs is equipped to sufficiently protect




Figure 2. Electronic Tap Changer.

against the full range of lightning-induced power-line problems. For broader protection, users should consider more sophisticated regulators, power conditioners and uninterruptible power systems (UPS).

The ferroresonant regulator, also known as the constant voltage transformer, provides regulation for loads ranging from 15VA to 15,000VA. A complete static regulator, the ferroresonant regulator offers continuous readjustment of output voltage and

correction of sudden voltage changes. Input line voltage fluctuations of $\pm 15\%$ are reduced to $\pm 1/2\%$ at the output. Ferroresonant regulators also provide current limiting for overloads or short-circuits, and they inherently maintain output for brief power outages of up to 3ms. The ferroresonant regulator (Figure 3) protects against transients, as well as the sags, brownouts and micro-faults typically caused by lightning strokes.

SUSCEPTIBILITY SYSTEMS

Electromagnetic Field Generators— 10 kHz to 18 GHz from LogiMetrics

LogiMetrics, the specialist in EMI/RFI Susceptibility Test Equipment, gives you a turnkey system capability... from your concept through design and training.


Featuring:

- Broadband coverage, 10 kHz to 18 GHz
- 20 to 220 volts/meter, 1 meter from antenna
- Multi-antenna operation
- IEEE-488 GPIB programmability
- Systems and/or components available to meet specific requirements

For detailed information, call or write:


LogiMetrics, INC.

121-03 Dupont Street, Plainview, N.Y. 11803 • Phone: (516) 349-1700 • Telex: (510) 21-1833



Circle Number 167 on Inquiry Card

EMI/RFI noise can create havoc in sensitive electronic equipment, and in the case of many MIL-Spec applications, is forbidden. McLean Engineering has shielded packaged blowers and fans that can move cooling air into your enclosure while leaving the noise behind. Our engineers literally wrote the book on high efficiency, EMI/RFI shielded cooling, and we're ready now to pass on a powerful block of knowledge, and products, to you. Call us!



SHIELDED COOLING FOR ELECTRONICS

McLEAN ENGINEERING
DIVISION OF ZERO CORPORATION

70A Washington Road, Princeton Junction, NJ 08550 • 609-799-0100.

West Coast: Air Cooling Technology, 533 Constitution Avenue
Camarillo, CA 93010 • 805-987-5046.

Circle Number 217 For Telephone Contact.
Circle Number 218 For A Free Catalog.



Power Problems?

**SURGES!
SPIKES!
RFI/EMI!
DIPS!
SAGS!
BLACKOUTS!
BROWNOUTS!**

AEGIS™ . . . Power Conditioning Equipment . . . THE SOLUTION
Protects From Damaging Voltage Surges, Lost Data, & Costly Down Time



SPIKE-SPIKER®

Transient Voltage Suppressors & Noise Filters
Eleven Models — All Models Rated 120V, 15A

Deluxe Power Console—2-stage transient absorber; dual 5-stage filter; common & differential mode protection; nano seconds response; clamping at 150V; 8 individually switched sockets; fused; master switch; 7' cord and status lite. **\$97.95**



Quad Power Console—6-stage transient absorber; dual 5-stage filter; common & differential mode protection; pico second response; clamping at 131V; four outlets; fused; master switch; 7' cord and status light. **\$82.95**



Mini II—Direct AC Plug-In; 2-stage transient absorber; dual 3-stage filter; common & differential mode protection; nano second response; clamping at 150V; two outlets and status lite. **\$45.95**

LINE-SAVER™

Standby Uninterruptible Power System
—Clean Reliable Power System—

Model LS-240—240 watts—VA capacity—\$549⁰⁰

Model LS-480—480 watts—VA capacity—\$795⁰⁰

Back-up time: 11 min. full load, 27 min. 1/2 load, 43 min. 1/3 load; multiple-AC outlets, 3-staged transient protection; 4-staged RFI/EMI filter; sealed rechargeable internal battery; master control switch; test switch; external fuses; detachable 6' cord; external DC connectors for mobil use and extended hold-up time; many more exclusive features.



**INCREASE PROFITS
GOOD DEALER MARGINS**
SEND FOR DEALER PACKET

KALGLO®
6584 Ruch Rd., Dept. ITM86
Bethlehem, PA 18017
REPS-TERRITORIES AVAILABLE

Call or Write
800-524-0400
In Penna.
215-837-0700

Circle Number 221 on Inquiry Card

The electromagnetic regulator is a fast response static device for protecting larger systems with higher power loads. The correction of sudden voltage changes starts immediately, and is completed in less than 0.1 second. Input line voltage fluctuations of +10% to -20% are reduced to $\pm 0.05\%$ at the output. This design is available in power ratings up to 300kVA, in single-phase or three-phase configuration. It should be noted that, like electronic tap changers, these regulators typically provide little inherent noise protection. Surge suppressors and line filters can be added for power-line noise attenuation.

Power conditioners are an evolutionary advance above voltage regulators, providing excellent noise attenuation capabilities to computers, as well as voltage regulation. The portable micro/minicomputer regulator (MMR) represents a modification in ferroresonant regulator design to provide state-of-the-art noise rejection of 120dB in common mode and 60dB in transverse mode. There is a nominal trade-off in voltage regu-





Figure 3. Constant Voltage Transformer.

lation capabilities, however, as the MMR regulates input line variations of as much as $\pm 15\%$ to within $\pm 13\%$. Additionally, the MMR will

provide a minimum of 90% of nominal output voltage at 65% of rated input voltage.

Where critical electronic equip-



PEARSON

Wide Band, Precision

Current Monitor

With a Pearson current monitor and an oscilloscope you can make precise amplitude and waveshape measurement of ac and pulse currents from milliamperes to kiloamperes. Currents can be measured in any conductor or beam of charged particles, including those at very high voltage levels.

A typical model gives an amplitude accuracy of +1%, -0%, 20 nanosecond rise time, droop of 0.5% per millisecond, and a 3 db bandwidth of 1 Hz to 35 MHz. Other models feature 2 nanosecond rise time, or a droop as low as 1% per second.

Contact us and we will send you engineering data.

PEARSON ELECTRONICS, INC.
1860 Embarcadero Road, Palo Alto, Calif. 94303, U.S.A.
Telephone (415) 494-6444 Telex 171-412


Circle Number 54 on Inquiry Card



OHMIC FILTERS INC.

Specializing in *Custom Designs*
for Interference Control Products

(Military - Industrial - Medical Applications)



- Chokes/Line Coils
- RFI Power Line Filters
- Signal Processing Filters
- Surge Suppression Networks
- Low Leakage Medical Products

featuring:

- Low Price
- Fast Response
- Custom Designs
- Improved Performance

- Contact our Engineering Applications Department

OHMIC FILTERS INC.
P.O. DRAWER 1080
125 GRACE STREET
ST. MICHAELS, MARYLAND 21663
TELEPHONE 301-822-8504

Circle Number 224 on Inquiry Card




Figure 4A. SPS, under Normal AC Line Conditioning.




Figure 4B. SPS, during AC Voltage Droop or Failure.

ment must be protected against deep brownouts, emergency backup power may be necessary. This can be provided by either a UPS or a standby power source (SPS), although the range of other protective functions varies considerably between the two. A review of the SPS and UPS design characteristics will help clarify their capabilities.

The SPS — sometimes called an off-line UPS — consists of an inverter, battery, battery-charger and a high-speed transfer switch. Under normal ac line conditions, the inverter is at rest and the primary ac power feeds the critical load directly, or through optional filtering provided by the SPS. In the event of an ac voltage drop below a present transfer point (usually -15% of nominal), the load is transferred to the inverter, which will switch on the supply ac power converted from the battery. Figure 4.

The choice of an SPS depends largely on how much switching time the equipment to be protected will tolerate. Some highly sensitive electronics cannot tolerate the power lapses that occur during these



THE R&B EMI TRAINING INSTITUTE

AN INTENSIVE, SYSTEMATIC TWO-WEEK PROGRAM
DESIGNED TO PROVIDE NEW EMI ENGINEERS
WITH COMPREHENSIVE, IN-DEPTH INSTRUCTION
ON EMI PRINCIPLES, PRACTICES, AND TEST METHODS.

(Emphasis is on Military EMI Standards and Documentation.)

KEY TOPICS

- EMC Organization Structures and Responsibilities
- Basic Principles of Grounding, Bonding, and Shielding
- Filters, Gaskets, Suppressors and Other Design Aids
- Lightning/EMP/ESD Protection
- Radiation Hazards
- Design Problems/Practice
- Military Standards and Documentation
- Instrumentation and Test Methods/Hands-on Practice

BENEFITS

- Increased Productivity and Efficiency
- A Shortened Learning Curve
- Increased Morale and Higher Confidence Levels

The EMI Training Institute bridges the gap between college training and the EMC workplace. The program combines classroom instruction with hands-on testing, workshops, and problem sessions to give participants a thorough grounding and basic competency in EMC.

SPECIAL FEATURES

- Comprehensive, In-depth, practical training that cannot be matched by the occasional college course or seminar.
- A top-notch faculty of R&B engineers who share their practical experience, know-how, and insights.
- Workshops and problem sessions that allow participants to "learn by doing."
- Hands-on practice in a fully equipped EMI test facility.
- A "live-in" environment that provides plenty of opportunity for informal "one-on-one" sessions with the faculty and other participants.

ADMISSIONS

The Institute is open to new engineers and others who wish to broaden their knowledge of the EMI field. BSEE or equivalent is recommended.

TUITION

Tuition cost is \$2950, which includes course materials, full lunches, and breaks. (Room and board is additional.)

APPLICATIONS

Applications and more information can be obtained by writing to: Greg Gore, Director of Training, R&B Enterprises, 20 Clipper Road, West Conshohocken, PA 19428, or by calling 215-825-1960, Twx 510-660-8120, Fax 215-825-1684.

Circle Number 171 on Inquiry Card




Figure 5A. UPS, under Normal Operating Conditions.




Figure 5B. UPS, during AC Voltage Droop or Failure.

switches. Some SPS designs, however, incorporate high-speed transfer switches to help reduce these power lapses. These units offer switching times ranging between 4 and 10ms, which is an acceptable transfer time for most electronic devices.

Like the electronic tap changer, the SPS provides only limited protection from lightning-induced transients or noise. To gain these capabilities, the SPS would need an additional line filter and a surge arrestor, which may be offered as options with the SPS.

For critical applications that will not tolerate the switching time of the SPS, and for those that need protection against the full range of lightning-induced power problems, including blackouts, a "true" on-line UPS is the only alternative. Serving continuously as a power conditioner, the true UPS maintains output voltage within $\pm 13\%$ of nominal despite line fluctuations of $\pm 15\%$, providing continuous protection against over-voltage conditions and brownouts. The on-line UPS also protects against both common- and transverse-mode noise, with attenuation of at least 140dB over a broad frequency range.

Consisting of three major components — a rectifier/charger, a battery, and an inverter — the standard on-line UPS, under normal operating conditions, converts commercial ac power to dc by use of the rectifier/charger. The dc power charges the battery which runs the inverter section. The inverter then reshapes the dc power into ac, which supplies the critical load. Figure 5.

When a drop in the ac line power causes output from the rectifier/charger to decrease, the batteries automatically compensate for this drop and continue to provide dc power to the inverter. Since dc voltage is always present at the inverter input, neither a time delay nor switching is involved in maintaining the constant supply of clean, uninterrupted power. UPS operation continues with no break, and the critical load experiences no loss of power. When line power is restored, the UPS returns to normal operations, and the battery is automatically recharged by the rectifier/charger.


An economical alternative for obtaining backup power plus the benefits of conditioned power is to combine an SPS with a micro/minicomputer regulator, placing the MMR

downstream of the SPS. While the SPS/MMR combination does not offer the no-break power transfer provided by a true UPS, the SPS/MMR combination can provide a cost savings (as much as \$350) for protecting equipment that can tolerate the SPS switch-over delay time. However, the SPS/MMR combination has a longer recharge time than the UPS (from 8 to 16 hours for the SPS compared to 90 minutes to 3 hours for the UPS, depending on the model) and requires manual restart. (The UPS restarts automatically.)

Power protection equipment is available to provide a range of functions from simple filtering to total protection against lightning. Ultimately, the selection will depend as much on the importance of the

equipment as on the user's budget. In cases where backup power is not required, but broad range power conditioning is imperative, the micro/minicomputer regulator is recommended for providing both voltage regulation and isolation from disturbances. If protection against power failure is the only function needed, an off-line SPS can provide backup power economically to maintain continuous operation. But, if the equipment is performing a critical function and must remain on-line continuously, the extra cost of providing maximum protection with an on-line UPS should be weighed against all the expenses and liabilities that will be incurred if the unit is completely shut down or damaged by power problems. ■

PERMANENT PROTECTION FOR THE PERMANENT REFERENCE



Permanent Protection for the Permanent EMI-control Reference - **ITEM**. Custom-designed file cases and binders help you organize and preserve your own **ITEM** library, providing easy access and reference to EMI-control information. Each attractive navy leatherette case is embossed in silver, and holds up to six issues of **ITEM**.

Unconditionally Guaranteed!

CASES

- 1 for \$6.95
- 3 for \$20.00
- 6 for \$36.00

BINDERS

- 1 for \$8.50
- 3 for \$24.75
- 6 for \$48.00

(Outside USA, add \$2.50 per unit for postage and handling.)
In USA, allow 4 to 6 weeks for delivery.

Name _____

Company _____

Address _____

City/State/Zip _____

Send to: **Jesse Jones Industries (since 1843)**
Jesse Jones Building
Department ITEM
N.W. Corner "D" Street & Erie Ave.
Philadelphia, PA 19134

Environmental Protection Agency (EPA)
Office of Radiation Programs
 (ANR-461)-CM #2
 401 M St., S.W.
 Washington, DC 20460

Analysis and Support Division
 Mr. Norbert Hankin (703) 557-7380
 Ms. Doreen Hill (703) 557-7390

Electromagnetics Branch
 P.O. Box 18416
 Las Vegas, NV 89114
 Chief: Mr. Richard A. Tell (702) 798-2440
 Mr. Edwin D. Mantiply (702) 798-2436
 Mr. F. Paul Wagner (702) 798-2424

Federal Communications Commission
 Washington, DC 20554

Technical Analysis Div. (OST)
 Chief: Michael J. Marcus (202) 632-7040

Technical Analysis Division (OST)
 Tel: (202) 632-7040
 Chief: Michael J. Marcus

Technical Standards Branch (TSB)
 Authorization & Standards Div. OST
 Tel: (202) 653-6288
 Chief: Frank L. Rose
 George Harenberg
 John Reed
 Lillian Volcy

Federal Communications Commission
 P. O. Box 429
 Columbia, MD 21045

Authorization & Standards Div. (OST)
 Tel: (301) 725-1585
 Chief: Robert L. Cutts
 Deputy Chief: John T. Robinson

Experimental Engineering Branch (TAD)
Technical Analysis Div.
 Tel: (301) 725-1585
 Chief: Kenneth Nichols
 Asst. Chief: Hector Davis

Sampling & Measurements Branch (SMB)
Authorization & Standards Div.
 Tel: (301) 725-1585
 Chief: L. Art Wall
 Asst. Chief: Thomas Phillips
 Richard Fabina
 Joe Huwsay

Equipment Authorization Branch (EAB)
Authorization & Standards Div.
 Tel: (301) 725-1585
 Chief: Charles M. Cobbs
 Philip Inglis
 Bill Inglis
 Frank Copevich
 Ed Gibbons
 Errol Chay
 Hammond Dorsey
 Steve Dayhoff

National Aeronautics and Space Administration
 Goddard Space Flight Center
 Greenbelt, MD 20771

Mr. Gerald R. Taylor, Code 754.1
 Tel: (301) 344-5389
 Mr. James N. Scott, Code 860.1
 Tel: (301) 344-8003
 Mr. William B. Tereniak, Code 754.1
 Tel: (301) 344-6480
 Mr. Jay Levy, Code 302
 Tel: (301) 344-5298

National Aeronautics and Space Administration Headquarters
 Washington, DC 20546

Mr. John Kiebler, Code EC
 Tel: (202) 453-1515
 Mr. Harold Kimball, Code TS
 Tel: (202) 755-2480

National Aeronautics and Space Administration
 Langley Research Center
 Hampton, VA 23665
 Tel: (804) 827-3681

Mr. B. Dove (M/S 469) (804) 865-2233
 Mr. F. Pitts (M/S 130) (804) 865-3681

National Aeronautics and Space Administration
 Lyndon B. Johnson Space Center
 Houston, TX 77058

Mr. Robert L. Blount
 Code LA6 (713) 483-2708
 Mr. Arthur Reubens
 Code LN (713) 483-3441

National Bureau of Standards (NBS)
Electromagnetic Fields Div.
 Boulder, CO 80303
 Chief: Mr. C. K. S. Miller (303) 497-3131
 Mr. G. R. Reeve (303) 497-3557
 Dr. M. T. Ma (303) 497-3800
 Dr. N. S. Nahman (303) 497-5167

National Defence Headquarters
 Ottawa, Ontario, Canada K1A 0K2

Mr. J.H. Belanger, DASP 6-4
 Tel: (613) 993-1905
 Mr. M. J. Kuisma, QETE4-3 (819) 997-3571
 Mr. P. Barthia, DREO (613) 998-2218
 Mr. H. F. deWitt, DMCS 6 (613) 992-3314

National Telecommunications and Information Administration (NTIA)
 Department of Commerce
 Washington, DC 20230

Office of Spectrum Management
 Tel: (202) 377-1850
 Associate Administration: R.D. Parlow
 Deputy Assoc. Administration: W.D. Gamble

Office of Spectrum Plans and Policies
 Director: F. S. Urbany (202) 377-1138
 L. L. Bradley (202) 377-1138
 W. D. Gamble (202) 377-1138
 C. L. Hutchinson (202) 337-0805
 R. Reinke (202) 377-0805
 T. M. Walsh (202) 377-1138

Spectrum Engineering and Analysis Division
 179 Admiral Cochrane Drive
 Annapolis, MD 21401

Chief: G. F. Hurt (301) 261-8002
 Dep. Chief: P. L. Roosa (301) 261-8002

Chief, Systems Review Branch:
 R. Porter (202) 377-1164
 Chief, Spectrum Engrg. Branch:
 R. Hinkle (301) 261-8002
 Chief, Spectrum Analysis Branch:
 H. J. Y. Ng (301) 261-8002

Frequency Assignment and IRAC Admin. Support Division - Room 1605
 Dept. of Commerce
 Washington, DC 20230
 Chief: Anthony M. Corrado (202) 377-0319
 Chief: Frequency Assignment Branch
 R. Santilli (202) 377-1132
 Chief: IRAC Secretariat Branch/Executive Sect'., IRAC: E. Dinkle (202) 377-0599

Institute for Telecommunication Sciences
 Boulder, CO 80303
 Tel: 303-497-3000

Jean Adams (303) 497-5301
 Robert Matheson (303) 497-3293
 Leslie A. Berry (303) 497-5474
 Dr. Arthur D. Spaulding (303) 497-5201
 Ernest L. Morrison, Jr. (303) 497-5888

NATO Headquarters
US Air Delegation
Military Agency for Standardization
 APO New York 09667
 Tel: 011-322-241-0040
 Lt. Col. Bragg (Ext. 3603)

Naval Air Development Center
Code NADC 2034
 Warminster, PA 18974

Branch Head: R.F. Lane (215) 441-1881
 William T. Walker (215) 441-2906
 F. L. Malchman (215) 441-7051
 E. R. Schneek (215) 441-1367
 J. T. Daley (215) 441-7180
 Roger L. Hill (215) 441-3686
 D. P. Thomas (215) 441-2999
 R. D. Bonner (215) 441-3762
 M. Meer (215) 441-2038
 R. M. Parkinson (215) 441-7028
 K. Parson (215) 441-7047
 S. Ly (215) 441-2499

Naval Air Engineering Center
Code 945
 Lakehurst, NJ 08733
 Tel: (201) 323-7636

Mr. James Foster
 Ms. Carol Moore
 Mr. P. Mundy
 Mr. Thanh Nguyen
 Mr. D. Snedaker
 Mr. V. Tukiendorf
 Mr. R. Del Conte

Naval Air Systems Command
 NAVAIR 5161
 Washington, DC 20361

Mr. Tony Iaconna (202) 692-7788
 Mr. David Fellin (202) 692-7788

Naval Air Test Center
 Patuxent River, MD 20670

Electronics Systems Dept. (SY80)
 Tel: (301) 863-4797
 Mr. J. R. Seale
 Lt. Cdr. Roger Horn

EMC Section (SY82)
 Tel: (301) 863-4681
 Mr. R. A. Hammett (Sec. Hd.)
 Mr. J. L. Dawson
 Mr. F. W. Heather
 Mr. J. Kiger
 Mr. W. Fenwick
 Mr. M. G. Nahaj
 Mr. R. G. Fenwick
 Mr. J. Kmetz
 Mr. M. Squires
 Mr. W. K. P. Yung

Naval Avionics Center (NAC)
Code B/441
 6000 E. 21st St.
 Indianapolis, IN 46218

Robert Siefker (317) 353-7441
 Roland Brakensiek (317) 353-3986
 Dean Drigenberg (317) 353-4447
 Edward Guerra (317) 353-7468
 Keith Hines (317) 353-7468

Naval Civil Engineering Laboratory
 Port Hueneme, CA 93043
 Tel: (805) 982-4783
 J. L. Brooks

Naval Electronic Systems Engineering Activity
Code 2133
 St. Inigoes, MD 20684

Mr. Lewis R. Bachman (301) 862-8263
 Mr. Michael A. Gullberg (301) 862-8264
 Mr. Ken Oestreich (301) 862-8134
 Mr. Daniel Kilcoyne (301) 862-8137
 Mr. Richard Sharp (301) 862-8282
 Mr. Richard Harvan (301) 862-8893
 Mr. Thomas DeArmy (301) 862-8281

Naval Electronic Systems Security Engineering Center
 Washington, DC 20390-5270
 Tel: (202) 282-2252
 Mr. Jim Engles, NESSEC 350

Naval Electronics Engineering Activity, Pacific
 Box 130
 Pearl Harbor, HI 96860
 Tel: (808) 471-3686

Mr. Brian Kutara, Code 320BK
 Mr. Roy Uyeda, Code 320
 Mr. Steve Kobashigawa, Code 320SYK

Naval Ocean Systems Center
 San Diego, CA 92152

Mr. Glenn C. Salisbury, Code 822
 Tel: (619) 225-2646
 Mr. Robert Jordan, Code 951
 Tel: (619) 225-6450
 Mr. Robert Leffler, Code 954
 Tel: (619) 225-7641
 Dr. Marian Kvigne, Code 84
 Tel: (619) 225-7936
 Dr. J.W. Rockway, Code 805
 Tel: (619) 225-7302
 Dr. S.T. Li, Code 822
 Tel: (619) 225-6127
 Mr. James H. Schukantz, Code 822
 Tel: (619) 225-2646
 Mr. Terry Danielson, Code 951
 Tel: (619) 225-6450

Naval Operations, Office of Chief
Code OP-941F
 Washington, DC 20350
 Tel: (202) 695-2710

Mr. William J. Cook
 Dr. Robert J. Haislmaier

Naval Postgraduate School
Attn: Code 62AB
 Monterey, CA 93943
 Tel: (408) 646-2352
 Dr. Richard W. Adler