

Correlating DC resistance to the shielding effectiveness of an EMI gasket

Gaskets display a frequency dependence that is not necessarily a function of DC resistance.

THOMAS CLUPPER
W. L. Gore & Associates, Inc.
Elkton, MD

Traditionally, engineers predict how an EMI gasket will perform based on the DC resistance through the gasket. DC resistance is a reasonable indicator of how a gasket shields low frequency signals, but can be misleading about how the gasket performs at higher frequencies. Without getting into electromagnetic shielding theory, the purpose of a gasket is to create a continuous conductive path across a break or seam in a metal enclosure. If an electronic device could be entirely enclosed in a continuous metal box, it would not radiate outward or be susceptible to external radiation. However, breaks or seams in metal enclosures are necessary in order to access electronic devices for assembly or repair.

When the material within the gap, the EMI gasket, is not perfectly conductive, radiation from the enclosure can occur. This happens because the currents flowing on the inside of the enclosure create voltages across the gap, which can then be "transferred" to the outside of the enclosure and potentially radiate. Therefore, one would think that if the resistance across the gap is made as low as possible, the best shielding effectiveness (SE) possible could be achieved. This is only true if low resistance is achieved by placing a continuous, homogeneous gasket around

the perimeter of the seam. If low resistance is achieved by placing periodic grounding points, or screws, along the perimeter of the gap, the shielding effectiveness of the enclosure may change dramatically with frequency.

This frequency dependence comes from basic antenna theory that says when the dimensions of gaps or apertures approach the wavelength of the frequency of operation, radiation can occur. Therefore, if periodic conductive paths are used as the EMI gasket, the spacing between the contact points must be very small compared to the wavelength at the highest frequency. The following formula shows the relationship between frequency and wavelength:

$$\frac{c}{\sqrt{\epsilon_r}} = \lambda \cdot f$$

where

λ = wavelength

f = frequency

c = speed of light

ϵ_r = dielectric constant

Given this information, one could wonder: How does the DC resistance of a gasket correlate to shielding effectiveness? The answer is that it truly depends on the form of the EMI gasket and the environment, or enclosure, surrounding the gasket. A case study in which a coaxial test fixture is used to simulate the shielding environment of an enclosure sealed with an EMI gasket is used to illustrate this fact.

continued on page 242

It's a lightweight,
mesh-like
single-unit
structure
It wraps
It conducts heat
and electricity
contracts
and expands
It shields EMI, RFI and ESD

MicroGrid Precision Expanded Metal Foil
High performance characteristics: Up to 95% open area in most metals.
Call for a free sample.

DELKER
CORPORATION
16 Commercial St., PO Box 427, Branford, CT 06405 203/461-4277 FAX: 203/468-6902

Circle Inquiry No. 268

INSTY
*Panel*TM

- InstyJectorTM Handle System Patent Pending
- 4HP - 8HP - 12HP Width by 6U Length
- Rapid-Custom Fascia Development
- Efficient Panel Construction
- Maximum EMI Shielding
- Completely Assembled

World class VME panels
for advanced requirements
and laboratory applications

Production quantities of
10 to 10,000 units all built to
your custom fascia specification

INSTYTM

Toll Free 800 662 4940
Fax 612 425 4835
Web <http://www.insty.org>
Email jbryan@insty.org

8616 Xylon Avenue North, Suite H
Brooklyn Park, Minnesota 55445-1821

Circle Inquiry No. 78

Correlating DC resistance ...
continued from page 59

CASE STUDY

Using the case where an EMI gasket is used in the far field of an incident electromagnetic signal, its ability to shield the signal can be defined by comparing the transmitted signal to the incident. This transmission coefficient (τ) can be expressed as shielding effectiveness, in decibels, if $20 \log(\tau)$ is computed. A way of actually measuring this phenomenon is to use coaxial transmission lines to simulate the TEM, plane wave propagation. This technique has been used for many years as a method of determining the relative shielding effectiveness of EMI gasket materials. The conductive gasket, shaped as an annular ring, creates a short circuit between the inner conductor and outer conductor (Figure 1).




Figure 1. Diagram of test fixture.

At sufficiently low frequencies, the size of the gasket is much smaller than the wavelength. This means that the effect of the gasket can be represented as a "lumped" equivalent circuit at the junction of the gasket, as shown in Figure 2.

The transmission coefficient for the above model would be as follows:

$$\tau = \frac{2Z}{Z_0 + 2Z}$$

where

Z_0 = characteristic impedance

Z = gasket impedance

and the shielding effectiveness (SE) would be expressed as

$SE = 20 \log(\tau)$.

If the impedance of the gasket is as-

one
with a
pula-
shells
ng of

ed up
think

is or
neuro
tally
is no

om

that
e of
true
face

vi: to
that
1 ter-

y and
in to

i with
ervice

n like

g 2: a
be the

1864)
13-21


Shetland wool *n.* (1790) : fine wool from sheep raised in the Shetland islands; also: yarn spun from this

sheugh \shuk\ *n.* [ME *sough*, fr. *swoughen* to *sough* – more at *SOUGH*] chiefly *Scot* (1501) : DITCH, TRENCH


shield \she(e)ld\ *n.* [ME *sheld*, fr. OE *sciold*; akin to OE *sciell* shell] (bef. 12c) 1 : a broad piece of defensive armor carried on the arm 2 : one that protects or defends : DEFENSE 3 : DRESS SHIELD 4 : a fixture designed to protect persons from injury from moving parts of machinery or parts carrying electricity

shield *vt* (bef. 12c) 1 **a** : to protect with or as if with a shield : provide with a protective cover or shelter **b** : to cut off from observation : HIDE 2 **obs** : FORBID **Syn** see DEFEND—Shield•er *n*


Shielding Express \ *n.* 1 : the fastest way to solve RF/EMI problems using wire mesh gaskets, elastomer gaskets, vents and air filters in commercial, MIL-STD and custom configurations 2 : a shielding manufacturer who cross-references part numbers from all other shielding manufacturers 3 : a shielding manufacturer who quotes your requirements in 24 hours.



VENTS AND
AIR FILTERS



WIRE MESH
GASKETS



ELASTOMER
GASKETS



Route 140 Industrial Park
29 Mozzone Boulevard
Taunton, MA 02780
tel: 508-880-0987 fax: 508-880-0334

• Contact us for further information •

Circle Inquiry No. 143

SOLUTIONS

FROM AN ESTABLISHED AND RECOGNIZED
LEADER IN THE INDUSTRY

- MICROWAVE ABSORBERS
- ANECHOIC CHAMBERS
 - Design
 - Manufacturer
 - Installation
 - Test

CUSTOMIZED
SOLUTIONS
ENGINEERING • FULFILLMENT • SUPPORT



**CUMING MICROWAVE
CORPORATION**

225 BODWELL ST • AVON, MA 02322

1-800-432-6464

(508) 580-2660

FAX: (508) 584-2309

E-mail: mwsales@cummingcorp.com
www.cummingcorp.com

Circle Inquiry No. 159

sumed to be equal to the DC resistance, R , across the gap, then for a typical 50-ohm line the expression becomes:

$$\tau = \frac{R}{25 + R}$$

If this expression is plotted in terms of shielding effectiveness as a function of DC resistance, Figure 3 results.

TEST PROCEDURE

In order to collect actual data based on the above model, an EMI gasket test fixture, similar to the one in the case study, was used. For the gasket under test, two different materials were selected, Gasket A and Gasket B. Both were about 0.015 inches thick and 0.040 inches wide. First, the SE data was collected with the fixture connected to a network analyzer. Then the actual DC resistance of the gap was measured with the gasket still in place, using a special probe and a micro-ohm meter. Using Figure 3, one would expect the measured DC resistance to correlate well to the low frequency shielding effectiveness.

RESULTS

Figure 4 shows the measured shielding effectiveness of the two gasket materials. Gasket A performed better than Gasket B, but Gasket B displays significant improvement in shielding performance with frequency. When the DC resistance was measured across the gasket while still in the fixture, the results were approximately 1 ohm for Gasket B, and 10 milliohms for Gasket A.

Referring to Figure 3, 1 ohm correlates to 28 dB of shielding effec-





Figure 2. Lumped equivalent circuit of gasket junction.

Enhance Microwave Performance



Registered
ISO 9001

ECCOSORB®, Emerson & Cuming Microwave Product's complete range of microwave absorbing materials, effective in controlling electromagnetic interferences from 0.8 through 40 GHz. Products Include:

- Cavity damping-surface current absorbing elastomers & foams
- Broadband & tuned specular absorbing elastomers & foams
- Lossy magnetic machinable rod & sheet series for terminations & loads

We specialize in providing custom shaped ECCOSORB® absorbing materials, ECCOSTOCK®, dielectrics and ECCOSHIELD® shielding products.

**EMERSON
& CUMING**
MICROWAVE PRODUCTS


*the recognized global leader in
microwave absorbing materials.*

800-650-5740


28 York Avenue, Randolph, MA 02368
781/961-9600 • fax 781/961-2845
email-sales@emersoncumingmp.com
www.emersoncumingmp.com

NEW!! Microwave Absorbers in Sheet Form & Suppressant Tubing Form

New highly dissipative microwave absorbers utilize lossy materials to provide high attenuation above 100 dB over a broad range of bandwidths up to 100 GHz. Available in adhesive backed sheets of various sizes and thicknesses, they can be cut with scissors and fitted to odd shapes. These absorbers can be used to line walls of enclosures and for free space use. They can also be used for waveguides and antenna elements, for modifying surface currents, as terminations, reflectors and for other microwave applications. Tubing can be slipped over existing wires and cables, and can be used for gasketing.



**23 NASSAU AVE.
INWOOD, NY 11096-1615
(516) 371-5600
FAX: (516) 239-5481**



*Free samples and literature
available upon request.*

Circle Inquiry No. 45




Figure 3. Predicted low-frequency shielding effectiveness based on DC resistance.

tiveness, and 10 milliohms correlates to 68 dB of shielding effectiveness. Comparing these predicted results to the actual results shown in Figure 4, we see that the low frequency shielding correlates to our simple model. However, it is apparent that this model does not predict what happens at higher frequencies. It is a complex task to accurately model all of the higher frequency effects of the EMI gasket junction. Even skin effect losses and transmission line effects do not explain the high frequency behavior of typical gasket materials.

To illustrate this point further, three 0.33-ohm, 1210-SMT chip resistors were placed around the perimeter where the gasket would normally go, to act as a three-point grounding EMI solution. These resistors were placed at 120° increments around the annulus, and used as contacts between the center conductor and the outer conductor.

Figure 5 indicates that the actual low frequency shielding effectiveness is about 46.7 dB. The actual DC resistance across this gap was measured to be 0.121 ohms. If this number is plugged into the formula, a





Figure 4. Measured shielding effectiveness of gaskets.

The MAJR Difference!



SAVE TIME!


SAVE MONEY!

MAJR Products Corp. provides EMI/RFI Elastomers, Gasketing, Shielding, Ventilation/Filtration Panels that meet or exceed the requirements of your current supplier.

Call today to find how prompt, courteous service and fast turnaround will make the "MAJR" difference in your product requirements.


MAJR PRODUCTS CORP.

P.O. Box 699 / 600 Erie Street / Saegertown, PA 16433
(814) 763-3211 / fax (814) 763-2952



Circle Inquiry No. 210

**ISO 9001
Certified Facilities**



**Shielded
Cooling
For
Electronics**

**McLean Thermal
Management** East

2 Applegate Drive • Robbinsville, NJ 08691
(609) 208-1900 FAX (609) 208-1902

Mailing Address - P.O. Box 10650
Hamilton, NJ 08650-2007

EMI/RFI NOISE CAN CREATE HAVOC IN SENSITIVE ELECTRONIC EQUIPMENT, AND IN THE CASE OF MANY MIL-SPEC APPLICATIONS, IS FORBIDDEN. McLEAN ENGINEERING HAS SHIELDED PACKAGED BLOWERS AND FANS THAT CAN MOVE COOLING AIR INTO YOUR ENCLOSURES WHILE LEAVING THE NOISE BEHIND. OUR ENGINEERS LITERALLY WROTE THE BOOK ON HIGH EFFICIENCY, EMI/RFI SHIELDED COOLING, AND WE'RE READY NOW TO PASS ON A POWERFUL BLOCK OF KNOWLEDGE AND PRODUCTS TO YOU. CALL US!

Circle Inquiry No. 218




Figure 5. Measured shielding effectiveness of three resistors.

predicted SE of 46.3 dB results. Therefore, the low frequency values correlate very well, but the high frequency shielding does not, becoming almost zero above 1.81 GHz. The reason for this is that at the point where the signal $\frac{1}{4}$ wavelength approaches the separation distance, or chord, between the grounding points (approximately 1.6 inches), the slot would be expected to radiate (approximately 1.85 GHz).

SUMMARY

In theory, if one could create an EMI gasket from perfectly homogeneous materials, then a model could be produced that would predict the higher frequency effects of shielding performance. The model would include factors like the DC resistance of the gasket, skin effect losses, absorption, and transmission line effects, and would only be accurate for this kind of test fixture. However, in real life enclosures, practical EMI gaskets made from metal springs, metal spring fingers, conductive particle-filled elastomers, etc., display a frequency dependence that is not necessarily a function of the DC resistance of the gasket.

THOMAS CLUPPER has been with Gore for 14 years and is currently the RF/microwave technologist for the GORE-SHIELD® family of EMI solutions. GORE-SHIELD® is a registered trademark of W. L. Gore & Assoc., Inc. Tom was instrumental in developing gasket material advances through proprietary modeling software and characterization using internally-designed coaxial fixtures and mode-stirred chambers. (410) 392-3800.

**More shielding aids
articles on RBitem.com
The EMC source**