

Using CAE to Design Magnetic Shielding Solutions

NICHOLAS F. CAMPAGNA, Campagna Consulting
CURTIS REBIZANT, Integrated Engineering Software

INTRODUCTION

Electromagnetic designs are found in a wide variety of industrial and R&D applications: cables, magnetic shielding, transmission lines, high voltage systems, and other EM systems. Engineers need to understand the electromagnetic behaviors (e.g., fields, forces, eddy currents, etc.) of these designs so that costs and performance can be effectively managed. In the past, engineers were limited to costly prototyping or restrictive analytic models. Today, engineers use electromagnetic computer-aided engineering (EM-CAE) software tools that provide cost effective design solutions.

CAE — BOUNDARY ELEMENT TECHNOLOGY

Two distinct numerical approaches exist for EM-CAE software tools: the finite element method (FEM) and the boundary element method (BEM). While the FEM approach, based on a differential formulation, is more familiar to engineers, the BEM approach offers some unique advantages. BEM is based on solving Maxwell's equation in the integral form. The BEM approach requires only the design's surface to be modeled with boundary elements in contrast to the FEM approach which requires the design's entire domain, including free space, to be modeled with a finite element mesh. This means the BEM model is an order of magnitude less complex than the FEM model.¹ BEM allows for easy visualization of the element distribution, especially for three-dimensional designs where FEM meshes are all but impossible to represent and comprehend.

To even model the behavior of a

BEM can provide designers with an alternative numerical approach to magnetic shield design.

two-dimensional electromagnetic design, FEM techniques require meshing of the design's structural walls, and the design's internal and external regions (Figure 1). Also, a FEM mesh must be created inside the design's structural walls. For BEM, the boundary elements are distributed only on the design's walls (Figure 2). BEM solutions are easier to use and consume smaller amounts of computer storage and analysis time than FEM solutions.

MAGNETIC SHIELDING BACKGROUND

One suitable application for the BEM approach is magnetic shielding in nuclear magnetic resonance (NMR) systems. NMR imaging is a vital part of the radiologist's suite of imaging techniques and it requires a very homogeneous magnetic field. Traditionally, a large superconducting solenoid with current density in its coils

on the order of 15,000 to 20,000 A/cm² is used to create the magnetic field. Given a current density J on three defined coil pairs in space, the radial and axial extent of the 5-gauss (G) line can be determined via analytical or numerical means.

Design issues arise because the 5-G line's spatial extent from a 1-m warm bore superconducting magnet affects other critical hospital space. Magnetic shielding is used to reduce the fringe field of a 15,000-G magnet to that of a 3,000-G magnet, thus making adjoining hospital rooms more useful for other radiological procedures. Three design parameters must be considered when designing the shielding:

- 5-G radial and axial extent
- magnet's homogeneity
- shield's size and weight

The shielding's interior size is fixed by the magnet's outer vacuum vessel and by the need to center the magnet coils inside the shielding. Coil centering is required to avoid differential forces between the coils and the shield's interior, which can easily destroy a \$400,000 magnet. The ability to simulate the different coil positions within the ferromagnetic structure and calculate the forces is therefore important. With




Figure 1. Two-dimensional FEM Mesh.




Figure 2. Two-dimensional BEM Mesh.

Continued on page 250




Figure 3. Magnetic Shielding: Magnetic Fields from Two-dimensional Axisymmetric Model.




Figure 4. Magnetic Shielding: Three-dimensional Model with Boundary Elements.

| | 15,000 G No Shield | 15,000 G With Shield | 2,500 G No Shield |
|------------|--------------------------|----------------------------|-------------------------|
| 5-G Axial | 1205 cm | 696 cm | 670 cm |
| 5-G Radial | 947 cm | 471 cm | 515 cm |

Table 1. Final Cylindrical Configuration.

FEM analysis the task is extremely difficult because of the remeshing required during iterative modeling of the system's complex three-dimensional, asymmetric structure. In BEM no remeshing is required as only the interfaces between permeable materials are meshed. The objects in BEM analysis are easily modified in an arbitrary magnetic field. This simplifies simulating the relationship between the sources (coils, permanent magnets, earth's magnetic field, etc.) and the permeable materials such as non-linear iron.

MAGNETIC SHIELDING SIMULATION

Starting with a known magnet coil arrangement, the coils and the outside of the magnet were modeled to determine the 5-G line's radial and axial extent and the base magnet homogeneity. At this stage, a simplified perfect cylinder two-dimensional axisymmetric model was used² (Figure 3). The shielding ratios were estimated by comparing the simulated results to the design requirements. Magnetic shielding shunts the field between the magnet's poles. It does not shield, in the conventional sense, as lead does with ionizing radiation via an absorption mechanism. Generally, NMR systems require a magnet to be homogeneous to within ± 5 ppm over a 50-cm diameter spherical volume.

The strength limits of the shim set used to adjust the magnet were determined and used as the acceptance criteria of the analysis. Five parameters were changed during simulation:

- shell wall thickness
- inside diameter of the shell
- length of the shell
- end cap wall thickness
- inside diameter of the end cap

The spherical and tesseral harmonics of the shield were calculated analytically from simulated data for the various sizes and compared to the shimming strength of the magnet shim set (active and passive), while still satisfying the 5-G line design requirements. As a result, the second and fourth order harmonics were the dominant ones of the shield, with the second being the most variable. It was strongly controlled by the interior diameter of the end cap, which also controlled the axial extent of the 5-G line. A shield size was selected and at this point the simplified perfect cylinder two-dimensional axisymmetric model of the shield was converted to the complete non-perfect cylinder three-dimensional model³ (Figure 4).

Holes for the magnet legs, cryogen fill ports, quench burst port, and supports were placed in the three-dimensional model, and an analysis was run in both centered and non-centered coil conditions. The results were acceptable and a prototype was constructed. The magnet came up to field, shimmed, and met specification on the first try. Simulated results matched design requirements, and the design was released to production. The shield's final cylindrical configuration is given in Table 1.

Similar techniques have been used to design close-fitting shields for 12T and 14T (120,000-G and 140,000-G) ion cyclotron magnets.

If the magnetic shielding had been designed using FEM, each iteration would have required tedious FEM remeshing because of test changes to shield components. BEM-based electromagnetic software tools offer engineers a proven and effective method for reducing design costs and optimizing designs of magnetic shielding sys-

tems because no remeshing is required when adjusting shield components.

SUMMARY

The introduction of new technology like the boundary element method (BEM) is meant to simplify and enhance engineering work environments. The magnetic shielding application confirms that the BEM approach can provide designers with an alternative numerical approach to magnetic shield designing. Such CAE tools enhance engineering productivity and increase competitive advantages.

REFERENCES

1. Y.B. Yildir, "Computer-Aided Magnetic Field Analysis Using the Boundary Element Method," Proceedings of the ICWA, pp. 36-40, Cincinnati, Ohio, October 3-6, 1988.
2. MAGNETO: Users and Technical Manual, Integrated Engineering Software Inc., 46-1313 Border Place, Winnipeg, Manitoba, Canada, R3H 0X4, 1994.
3. AMPERES: Users and Technical Manual, Integrated Engineering Software Inc., 46-1313 Border Place, Winnipeg, Manitoba, Canada, R3H 0X4, 1994.

NICHOLAS F. CAMPAGNA of Campagna Consulting, Menomonee Falls, Wisconsin, has an M.E. in electrical engineering from Stevens Institute of Technology, Hoboken, N.J. and an M.S. degree in biomedical engineering from Case Western Reserve University, Cleveland, Ohio. He is a systems and design engineer experienced in FEM (magnetic and structural), and BEM (magnetic) computer-aided design analysis techniques, including design and analysis of high power PM-BLDC, and of SR motors and limited angle torque actuators (LATA). He may be contacted at (414)253-1027.

CURTIS REBIZANT is an engineer at Integrated Engineering Software, which produces and markets software for electromagnetic system simulation. He has a B.S. in electrical engineering from the University of Manitoba and has extensive experience with electromagnetic CAE software. He may be contacted at Integrated Engineering Software, Winnipeg, Manitoba, Canada, R3H 0X4, (204)632-5636.

MAGNETIC SHIELDING



- CO-NETIC (high permeability) Sheet and Foil from Stock
- NETIC (high saturation) Sheet and Foil from Stock
- Shields for CRTs, PMTs, Transformers and Medical Instruments
- Custom Shields — Prototype through Production
- Engineering, Design and Test Facilities

USE OUR LAB KIT TO SOLVE
MAGNETIC SHIELDING PROBLEMS
Order LK-120 \$129.00

MAGNETIC SHIELD CORP.
Perfection Mica Company
740 North Thomas Drive • Bensenville, Illinois 60106 U.S.A.
Fax 708-766-2813 Phone 708-766-7800 or 800-304-5665

*Call Today
For Our
New
Catalog!*



Circle Inquiry No. 111

Spang

Specialty Metals
P.O. Box 391
Butler, PA 16003
(412) 282-1515
Fax 412-282-4209

The Company Behind The Name

For over 25 years we have been a quality supplier of MuMetal, a Spang Specialty Metals registered trademark. We would be pleased to quote on your annual requirements as well as your emergency fill-in needs.

Please call Kelly Schmidt at (412) 282-1515.

MuMetal

Circle Inquiry No. 74